


CC4V-T1A

Tuning Fork Crystal 30 kHz – 1.0 MHz



DIMENSIONS



All dimensions in mm typical

APPLICATIONS

Metering
Industrial
Automotive
Health Care
Medical Implantable
Harsh Environments

DESCRIPTION

The CC4V-T1A is a low frequency SMT Quartz Crystal Unit that incorporates a tuning fork Quartz Crystal Resonator. It operates under vacuum in a hermetically sealed ceramic package with ceramic lid.

FEATURES

Mature product for harsh environments.
Outstanding hermetic sealing with gold-tin preform.
High stability and low aging guaranteed by hermetic sealing.
Available for extended operating temperature range.
High shock and vibration resistant.
100% Pb-free, RoHS-compliant.
Automotive qualification according to AEC-Q200 available.

ELECTRICAL CHARACTERISTICS AT 25°C

Frequency Range	F _L	30–200	201–560	1'000	kHz
Load capacitance ¹⁾	C _L	6.0	9.0	7.0	pF
		7.0			
		9.0			
		10.0			
		12.5			
Frequency tolerance ²⁾	ΔF/F	±20	±100	±100	ppm
	ΔF/F	±100	±250	±500	ppm
Drive level max.	P	1.0			μW
Insulation resistance min.	R _i	500			MΩ
Aging first year max.	ΔF/F	±3			ppm

Standard Frequencies ³⁾	F _L	32.768	200.000	1'000	kHz
Series resistance typ./max.	R _S	50 / 65	3.2 / 5.0	0.5 / 1.0	kΩ
Motional capacitance typ.	C ₁	2.1	2.1	2.1	fF
Static capacitance typ.	C ₀	1.2	1.3	1.0	pF
Turnover temperature	T ₀	25 ±5	30 ±5	32 ±5	°C
Frequency vs. temperature	ΔF/F ₀	-0.035 ppm/°C ² (T - T ₀) ² ±10%			ppm

STANDARD FREQUENCIES

Frequencies			
32.768 kHz	38.400 kHz	40.000 kHz	100.000 kHz
128.000 kHz	153.600 kHz	200.000 kHz	1.0000 MHz
Other frequencies on request			

ENVIRONMENTAL CHARACTERISTICS

		Conditions	Max. Dev.
Storage temp. range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
TB Extended oper. temp. range		-40 to +125°C	
TC Extended oper. temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	±5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	±5 ppm

TERMINATIONS AND PROCESSING

Type	Termination	Processing
CC4V-T1A	For SMT mounting Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s
CC4V-T2A	SnPb plated pads available on request	

ORDERING INFORMATION

C C 4 V - T 1 A 32.768 kHz 12.5 pF ±20 ppm TA QC

<p>Ceramic package ———</p> <p>Ceramic lid ———</p> <p>Package size ——— 4 = 5.0 x 1.9 x 0.9 mm</p> <p>Tuning fork ———</p> <p>SMT Package ———</p> <p>Pads ——— 1 = Au flashed pads 2 = SnPb plated pads</p> <p>Pads on both ends ———</p>	<p>Frequency F_L ——— 32.768 kHz</p> <p>Load capacitance C_L ——— 6.0 pF, 7.0 pF 9.0 pF 10.0 pF 12.5 pF Other C_L on request</p> <p>Frequency tolerance ——— ±20 ppm, ±100 ppm ±250 ppm, ±500 ppm Tighter freq. tolerances on request</p> <p>Temperature range ——— TA = -40 to +85°C (Standard) TB = -40 to +125°C TC = -55 to +125°C</p> <p>Qualification ——— QC = Commercial Grade (Standard) QA = Automotive Grade AEC-Q200 QM = Medical Grade</p>
---	--

A unique part number will be generated for each product specification, i.e:	
20xxxx-MG02	2'000 pcs (in 12 mm tape on 7" reel)
20xxxx-PG10	10'000 pcs (in 12 mm tape on 13" reel)

All specifications subject to change without notice.