



TCXO / VC-TCXO

ULTRA HIGH STABILITY


TG5032CBN

TG5032SBN

- Frequency range : 10 MHz to 50 MHz
- Supply voltage : 3.3 V Typ. / 5.0 V Typ.
- Frequency / temperature characteristics : $\pm 0.28 \times 10^{-6}$ Max. (for Stratum3)
- Frequency aging : $\pm 3.0 \times 10^{-6}$ Max./20years(for Stratum3)
- External dimensions : 5.0 × 3.2 × 1.45 mm (10 pins)
- Applications : Network synchronization, Stratum3, Microwave BTS
- Features : Ultra high stability



Product Number (please contact us)
TG5032CBN : X1G004571xxxxxx
TG5032SBN : X1G004581xxxxxx



Actual size



Specifications (characteristics)

Item	Symbol	TG5032CBN (CMOS)		TG5032SBN (Clipped sine wave)		Conditions / Remarks
		VC-TCXO	TCXO	VC-TCXO	TCXO	
Output frequency range	f_o	10 MHz to 50 MHz 10, 12.8, 15.36, 16.384, 19.44, 20, 24, 24.576, 25, 26, 27, 30.72, 40, 49.152, 50 MHz				Standard frequency
Supply voltage	V_{CC}	C: 3.3 V $\pm 5\%$, H: 5.0 V $\pm 5\%$ (Supply voltage range : 2.7 V to 5.5 V)				
Storage temperature	T_{stg}	-40 °C to +90 °C				Storage as single product
Operating temperature	T_{use}	G: -40 °C to +85 °C				
a) Frequency tolerance	f_{tol}	$\pm 1.0 \times 10^{-6}$ Max. (10 MHz $\leq f_o \leq 40$ MHz) $\pm 0.9 \times 10^{-6}$ Max. (40 MHz $< f_o \leq 50$ MHz)				After reflow, +25 °C
b) Frequency/temperature characteristics	f_o -Tc	B: $\pm 0.28 \times 10^{-6}$ Max. (for Stratum3) H: $\pm 0.25 \times 10^{-6}$ Max. (for Stratum3) : Option				-40 °C to +85 °C
c) Frequency/load coefficient	f_o -Load	$\pm 0.1 \times 10^{-6}$ Max. (10 MHz $\leq f_o \leq 40$ MHz) $\pm 0.2 \times 10^{-6}$ Max. (40 MHz $< f_o \leq 50$ MHz)				Load $\pm 10\%$
d) Frequency/voltage coefficient	f_o -Vcc	$\pm 0.1 \times 10^{-6}$ Max. (10 MHz $\leq f_o \leq 40$ MHz) $\pm 0.2 \times 10^{-6}$ Max. (40 MHz $< f_o \leq 50$ MHz)				Vcc $\pm 5\%$
e) Frequency aging	f_{age}	$\pm 0.5 \times 10^{-6}$ Max. $\pm 3.0 \times 10^{-6}$ Max. (for Stratum3)				+25 °C, First year +25 °C, 20 years
Holdover stability (Constant temperature)	-	$\pm 0.01 \times 10^{-6}$ Max. (+25 °C, 24 hours) $\pm 0.04 \times 10^{-6}$ Max. (+25 °C, 24 hours)				After 10 days of continuous operation.
Free-run accuracy	-	$\pm 4.6 \times 10^{-6}$ Max.				After 48 hours of continuous operation.
Current consumption	I_{cc}	5.0 mA Max. / 6.0 mA Max. 6.0 mA Max. / 8.0 mA Max. 8.0 mA Max. / 10.0 mA Max.		5.0 mA Max.		This includes Item a), b), c), d) and e) 10 MHz $\leq f_o \leq 26$ MHz (3.3V / 5.0V) 26 MHz $< f_o \leq 40$ MHz (3.3V / 5.0V) 40 MHz $< f_o \leq 50$ MHz (3.3V / 5.0V)
Input resistance	R_{in}	100 k Ω Min.	—	100 k Ω Min.	—	Vc- GND (DC)
Frequency control range	f_{cont}	$\pm 5 \times 10^{-6}$ to $\pm 10 \times 10^{-6}$	—	$\pm 5 \times 10^{-6}$ to $\pm 10 \times 10^{-6}$	—	J,D : Vc=1.5 V ± 1.0 V at Vcc=3.3 V K,E : Vc=1.65 V ± 1.0 V at Vcc=3.3 V L,H : Vc=2.5 V ± 2.0 V at Vcc=5.0 V
Frequency change polarity	—	Positive polarity	—	Positive polarity	—	
Symmetry	SYM	45 % to 55 %	—	—	—	GND level (DC cut)
Output voltage	V_{OH}	90 % Vcc Min.	—	—	—	
	V_{OL}	10 % Vcc Max.	—	—	—	
Output level	V_{PP}	—	—	0.8 V Min.	—	Peak to Peak
Rise time / Fall time	t_r/t_f	8.0 ns Max.	—	—	—	10% Vcc to 90 % Vcc level, Load: 15 pF
Start-up time	t_{str}	2.0 sec. Max. (Filter: Standard) / 5.0 ms Max. (Non-Filter: Option)				T=0 at 90% Vcc
Output load condition	Load	15 pF	—	10 k Ω /10 pF	—	
Input voltage	V_{IH}	70% Vcc Min.				OE terminal(Enable voltage)
	V_{IL}	30% Vcc Max.				OE terminal(Disable voltage)

* Note : Please contact us for requirements not listed in this specification.

Product Name
(Standard form)

TG5032 C BN 30.720000MHz C B G H N A

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Model ② Output (C: CMOS, S: Clipped sine wave)

③ Frequency ④ Supply voltage (C: 3.3 V Typ.)


⑤ Frequency/temperature characteristics (B: $\pm 0.28 \times 10^{-6}$ Max.) ⑥ Operating temperature (G: -40 °C to +85 °C)

⑦ OE function (H: Active High) ⑧ Vc function (Refer to symbol table) ⑨ Internal identification code ("A" is default)

⑧ Vc function (symbol table)					
Vc [V]	Non	1.5	1.65	2.5	Any
Filter ON	G	J	K	L	F
Non Filter	N	D	E	H	A


External dimensions

(Unit : mm)



Footprint (Recommended)

(Unit : mm)



PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.





WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

	► Pb free.
	► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc).

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied data, circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of customer damage or infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
/ Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.

SHENZHEN YIJIN ELECTRONICS CO: LTD TEL: 0755-27876565

18924600166 QQ: 857950243 <http://www.vc-tcxo.com>